

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

METHODS FOR EXTINGUISHING PETROLEUM-BASED FIRES,
SUPPRESSING PETROLEUM-RELEASED VAPORS AND CLEANING
PETROLEUM-CONTAMINATED SURFACES

ABSTRACT OF THE DISCLOSURE

[0052] Compositions and methods for emulsifying a petroleum product that has been spilled upon a portion of the earth's surface or that is burning are based upon use of a nonionic, primary surfactant composition comprising a first ethoxylated sorbitol oleate and, preferably, a second ethoxylated sorbitol oleate, and a nonionic, secondary surfactant that is capable of stabilizing and solubilizing the primary surfactant composition such that the resulting emulsifying compositions have a hydrophilic/lipophilic balance between about 12.0 and about 13.5.